

Automatic Gyroscopic Mixer

Tri-Direction Door

One Button Operation







Applications







- Automatic clamping, laborsaving;
- Best mixing performance for 2300-4500CP (105-136KU);
- Applicable to supermarket , warehouse , large/medium tinting center.


Item	Contents	Item	Contents
Mixing Mode	Gyroscopic	Clamping Mode	Automatic
Mixing Time	30-900s In 30s	Mixing Speed	150/200rpm
Mixing Range	1~36Kg	Can Size	90 ~ 400mm
Power Supply	220V/550Hz 110V/60Hz	Power	750W
Weight	240Kg	Dimension (WxDxH)	795×870×1050mm



Tri-Direction Door



- Tri-direction door, easy to open and close, open space.
- No need to bend over to open the door, labor-saving.








- Innovative design single motor, dual drive.
- One button operation for clamping; mixing; braking; and stopping.



Smart Detection



- Smart detection of big/small cans. Proper pressure and speed would be assigned accordingly.
- Applicable for single can mixing.



- Multiple small cans mixed simultaneously, efficiency greatly improved.
- Designated button for multiple cans mixing. Proper clamping pressure and speed would be assigned for better mixing performance.









LCD Screen

■ Running status; malfunctions; using times; and parameter settings clearly shown on the LCD screen.







Guide Screw Protection

■ Guide screw and pole equipped with covers for splash-proof function. Less maintenance.

■ Tri-Direction

Door, minimized footprint for operation.

Applicable Scenarios

■ Wide range of time selection: 30-900s.



■ Sealed electric components, fearless of dust.





SANTINT · CHINA

Address: Xushui Industrial Trade Park, Zhengzhou.

Tel:+86 371 6785 7168

SANTINT · POLAND

Address: ul. Postepu 19. mag.5 02-676 Warszawa Polska Email: info@santint.com

SANTINT · U.S.A

Address: 2000 Bloomingdale Road, Suite 220, Glendale Heights, IL 60139
Tel: +1 847 350 6911

SANTINT · AUSTRALIA

Address: 2/4 Weddel Court Laverton North Victoria Email: info@santint.com